



## **FIREPLAC® G-A2**

### **according to EN 13501-1**

#### **Oak euro [EEU1]**

Description:	FIREPLAC® G consists of a non-flammable gypsum board. It is covered with oak noble wood 0.6 mm and subsequently UV-varnished by europiac.
Fire protection class:	according to classification report: non-flammable, tested in compound according to EN 13501-1
Classification:	A2-s1, d0
Noble wood:	Oak euro 0.6 mm – UV-varnished
Carrier plate:	Plasterboard not combustible
Surface:	UV-varnished – matt, super matt, silk matt, silk gloss
Formats:	2600 x 1270 mm or 3030 x 1270 mm as well as fixed dimensions according to customer requirements
Thicknesses:	16 and 19 mm
Edges:	Testing incl. veneer edge 0.5 mm
Applications:	Furniture and interior design. Wall and ceiling claddings, panels, wall units, fire doors etc. Public buildings, offices, hotels, hospitals, kindergartens.

Vertrieb und Beratung:

...das beste aus holz!



Note: The material wood is a natural product.  
Characteristic are color and structure differences.  
These natural features qualify the precious wood material as real and give it a unique beauty.  
Samples and illustrations can only serve as a guide.

Vertrieb und Beratung:

...das beste aus holz!

Röhr GmbH . Narzissenstrasse 5 . D-88069 Tett nang  
Tel / Fax: +49.7542.9366.0 / 9366.60  
info@europiac.com . [www.europiac.com](http://www.europiac.com)

