



FIREPLAC[®] SE

Oak European[EEU1]

Description:	FiIREPLAC [®] SE is a flame retardant particleboard veneered with Noblewood oak in 0,6mm thickness and a UV lacquer final coating. Fireplac SE falls in the category of construction panels regulated by the building standard EN 3986. These fire-resistant panels are noble wood veneered lacquered and finished with edge banding.
Fire class rating	compound material rated as flame retardant according to EN 13501 – 1: 2007 + A1: 2009
Noblewood:	Oak european, 0,6mm – UV lacquered
Core Panel:	Fire retardant particleboard
Surface:	UV lacquered - matt, silk matt, super matt, silky gloss
Resin System	formaldehyde free
Edgebanding:	Fire test including edgebanding 0,5mm
Fields of Application:	Furniture and Interior Construction. Wall and Ceiling Panels, Wardrobe systems, Fire Doors Public Buildings, Offices, Hotels, Hospitals and nursery schools.

Vertrieb und Beratung:

...das beste aus holz!



Thickens	Formats available	Classification	Classification report
17mm	2800x2070mm	C-s2, d0	FIRES-CR-142-16-AUPE
19mm	2800x2070mm	C-s2, d0	FIRES-CR-142-16-AUPE
29mm	2655x2100mm	B-s1, d0	PK-18-090

As well as fix sizes according to customer specification



Vertrieb und Beratung:

...das beste aus holz!